



**UNIVERSITI PUTRA MALAYSIA**

**CROSSFLOW MEMBRANE  
TECHNOLOGY FOR CRUDE PALM OIL  
TREATMENT**

**RUSNANI ABD. MAJID**

**FK 2001 16**

**CROSSFLOW MEMBRANE  
TECHNOLOGY FOR CRUDE PALM OIL  
TREATMENT**

**RUSNANI ABD. MAJID**

**MASTER OF SCIENCE  
UNIVERSITI PUTRA MALAYSIA**

**2001**



**CROSSFLOW MEMBRANE TECHNOLOGY FOR CRUDE PALM OIL  
TREATMENT**

**By**

**RUSNANI ABD. MAJID**

**Thesis Submitted in Fulfilment of the Requirement for the Degree of Master  
of Science in the Faculty of Engineering  
Universiti Putra Malaysia**

**August 2001**



Abstract of the thesis presented to the Senate of Universiti Putra Malaysia in  
fulfilment of the requirement for the Degree of Master of Science

## **CROSSFLOW MEMBRANE TECHNOLOGY FOR CRUDE PALM OIL TREATMENT**

By

**RUSNANI ABD. MAJID**

**August 2001**

**Chairman : Dr. Fakhru'l-Razi Ahmadun**

**Faculty : Engineering**

Crude palm oil (CPO) is refined to quality edible palm oil by removing objectionable impurities such as free fatty acid (FFA), phospholipids, trace metals and colouring pigments which are detrimental to the flavour, odour, colour and stability of the oil. Conventional refining involves degumming, bleaching and deodorization steps. The energy-saving membrane technology is a physical separation process that can offer an alternative method to improve the conventional refining method by reducing energy cost and minimizing the waste disposal problem.

The objectives of this research study are to investigate the influence of membrane on the quality of CPO, to evaluate the operating conditions such as transmembrane pressure and feed flow, to study the performance of membrane with time, to establish the appropriate cleaning procedures for membrane, and to compare the quality of membrane-processed oil and conventional-processed oil as well as the storage stability of the oils.

CPO was filtered through microfiltration (MF) and ultrafiltration (UF) ceramic membranes. Two different pore sizes of MF membranes (0.2  $\mu\text{m}$  and 0.45  $\mu\text{m}$ ) and two pore sizes of UF membranes (20 nm and 50 nm) were used in the study. Comparison study was conducted for CPO treated with 0.2  $\mu\text{m}$  membrane. Ceramic MF membranes with pore sizes of 0.45 and 0.2  $\mu\text{m}$  rejected about 14% and 56.8% of phosphorus, respectively. The 0.2  $\mu\text{m}$  membrane removed more than 80% of the iron. Ceramic UF membranes with pore sizes of 50 and 20 nm rejected about 60% and 78.1% of phosphorus, respectively. The 20 nm membrane reduced about 60% of iron content. All membranes (MF and UF) showed no influence on carotene, FFA and fatty acid composition (FAC).

The MF membranes (0.2 and 0.45  $\mu\text{m}$ ) showed similar trend where the permeate flux for the membranes increased with average transmembrane pressure and feed flow until it reached a certain limit where the flux declined with increasing pressure and feed flow. Both membranes showed rapid flux decline during the initial stage, but stabilized for the period of 5 hr. Cleaning process was achieved by using Alconox detergent and acid/alkalis solutions.

The effect of pressure on flux for the 20 nm UF membrane showed similar trend with the MF membrane, but after 0.9 bar, the increased in flux was only slowed down rather than declining. The flux for the 50 nm UF membrane increased proportionally with pressure and no sign of flux decline was observed at 2.9 bar. The increase in flux at higher feed flow was only observed for the 20 nm membrane. Concentration polarization could have occurred for the 50 nm

membrane where the flux declined at higher feed flow. Cleaning for the UF membrane was more difficult than the MF membranes. The cleaning process involved cleaning with Alconox detergent, acid/alkalis solutions and soaking with solvents (hexane and isopropanol).

Reduction of phosphorus for oil treated with 0.2  $\mu\text{m}$  MF membrane was comparable with commercial bleached oil. FFA and carotene content were reduced after deodorization process. Carotene content and colour reading for membrane-processed oil was slightly higher than conventional-processed oil. The membrane process was unable to remove oxidation products as it was observed that the FFA and peroxide value were increased during the storage period.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia  
sebagai memenuhi keperluan untuk Ijazah Master Sains

**TEKNOLOGI MEMBRAN ALIRAN SILANG UNTUK  
PENGOLAHAN MINYAK SAWIT MENTAH**

Oleh

**RUSNANI ABD. MAJID**

**Ogos 2001**

**Pengerusi : Dr. Fakhru'l-Razi Ahmadun**

**Fakulti : Kejuruteraan**

Minyak sawit mentah ditapis menjadi minyak makan sawit dengan menyingkirkan bahan-bahan bendasing. seperti asid lemak bebas, fosfolipid, logam surih dan pigmen berwarna yang boleh merosakkan rasa, bau, warna dan kestabilan minyak. Penapisan lazim melibatkan beberapa peringkat pemprosesan seperti penyah-gam, perlunturan dan penyah-bauan. Penjimatan tenaga teknologi membran adalah proses pemisahan fizikal yang boleh digunakan sebagai kaedah alternatif untuk memperbaiki kaedah penapisan lazim. Ianya dapat menurunkan kos tenaga dan mengurangkan masalah sisa buangan.

Objektif kajian penyelidikan ini adalah untuk menyelidik pengaruh membran terhadap kualiti minyak sawit mentah, untuk menilai keadaan kendalian seperti tekanan udara dan kadar suapan, untuk mengkaji prestasi membran terhadap masa, untuk menetapkan cara cucian bagi membran, dan untuk membandingkan kualiti minyak yang telah diproses dari kaedah membran dan penapisan lazim disamping perbandingan terhadap kestabilan storan terhadap minyak.

Minyak sawit mentah telah ditapis menggunakan penapisan-mikro (MF) dan penapisan-ultra (UF). Dua saiz liang yang berlainan bagi MF (0.2  $\mu\text{m}$  dan 0.45  $\mu\text{m}$ ) dan dua saiz bagi UF (20 nm dan 50 nm) telah digunakan untuk kajian. Kajian perbandingan telah dijalankan bagi minyak sawit mentah yang telah ditapis dengan 0.2  $\mu\text{m}$  membran. MF membran seramik dengan saiz liang 0.45 dan 0.2  $\mu\text{m}$  masing-masing menyingkirkan lebih kurang 14% dan 56.8% fosforus. Membran dengan saiz liang 0.2  $\mu\text{m}$  menyingkirkan lebih dari 80% kandungan besi. UF membran seramik dengan saiz liang 50 dan 20 nm masing-masing menyingkirkan lebih kurang 60% dan 78.1% fosforus. Membran dengan saiz liang 20 nm mengurangkan lebih kurang 60% kandungan besi. Semua membran (MF dan UF) menunjukkan tiada pengaruh terhadap kandungan karoten, asid lemak bebas dan komposisi asid lemak.

Membran MF (0.2 dan 0.45  $\mu\text{m}$ ) menunjukkan aliran yang sama di mana fluks serapan bagi kedua-dua membran meningkat apabila tekanan udara dan kadar suapan ditingkatkan sehingga sampai ke satu peringkat di mana fluks mula menurun apabila tekanan udara dan kadar suapan meningkat. Bagi kajian terhadap masa, kedua-dua membran menunjukkan penurunan fluks yang laju di peringkat awal tetapi stabil sepanjang tempoh operasi selama 5 jam. Proses cucian dilaksanakan dengan menggunakan bahan cuci 'Alconox' dan larutan asid/alkali.

Kesan tekanan udara terhadap fluks bagi membran UF 20 nm menunjukkan aliran yang sama dengan membran MF pada peringkat awal



operasi. Walaubagaimanapun, peningkatan fluks berlaku dengan perlahan setelah 0.9 bar. Fluks untuk membran UF 50 nm meningkat berkadar dengan tekanan udara, dan tiada penurunan fluks pada 2.9 bar. Peningkatan fluks pada kadar suapan yang tinggi hanya didapati pada membran UF 20 nm. Kemungkinan pengutuban kepekatan telah berlaku terhadap membran 50 nm di mana fluks didapati menurun apabila kadar suapan dinaikkan. Cucian untuk membran UF adalah lebih rumit berbanding dengan membran MF. Process cucian melibatkan bahan cuci 'Alconox', larutan asid/alkali dan rendaman dengan pelarut (hexana dan isopropanol).

Pengurangan fosforus bagi minyak yang telah ditapis dengan proses membran (MF 0.2  $\mu\text{m}$ ) adalah setanding dengan minyak komersil yang terluntur. Asid lemak bebas dan kandungan karoten juga berkurangan setelah melalui proses penyah-bauan. Kandungan karoten dan bacaan warna bagi minyak yang telah diproses dengan membran didapati tinggi sedikit dari minyak hasil dari proses-lazim. Proses membran didapati kurang berupaya untuk menyingkirkan produk pengoksidaan setelah asid lemak bebas dan nilai peroksida menunjukkan peningkatan dalam tempoh simpanan.

## ACKNOWLEDGEMENTS

I would like to express my deepest gratitude and appreciation to Dr. Fakhru'l-Razi Ahmadun, the Chairman of my Supervisor Committee, for his valuable guidance, suggestions and advice throughout the course of my study till the preparation of this thesis. I also would like to express my greatest appreciation to Assoc. Professor Badlishah Sham Bin Baharin, one of the Supervisory Committee members, for his continuous support, encouragement and assistance. My grateful thanks also go to the other members of the Supervisory Committee, Assoc. Professor Dr. Shaari Bin Mustapha and Professor Dr. Yaakob Bin Che Man for their supervision, support and comment.

My sincere thanks and appreciation also go to all the laboratory staff, technicians of the Faculty of Food Science and Biotechnology, UPM and En. Hisham Bin Esa of Engineering and Processing Division, Malaysian Palm Oil Board who directly and indirectly assist and support in preparing this thesis.

I would like to acknowledge Malaysian Palm Oil Board for giving me the opportunity to pursue my M.Sc. study, Ministry of Science and Technology for awarding me the scholarship and Universiti Putra Malaysia for providing IRPA funding for this research.

Not the least but the most important, my special thanks to my loving husband Mohammad Ayob Bin Mohd Noor for his endless support, encouragement, patience and understanding throughout my studies. Lots of love



for my little golden baby Irfan Zikri who has brought the most happiness in my life and indirectly giving me the moral support. I also owe my grateful thanks to my family for their moral support and encouragement.

I certify that an Examination Committee met on 10<sup>th</sup> August 2001 to conduct the final examination of Rusnani Bte. Abd. Majid on her Master of Science thesis entitled “ Crossflow Membrane Technology for Crude Palm Oil Treatment” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Iyuke, Sunny Esayegbemu, PhD.,  
Department of Chemical Engineering and Environment,  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Chairman)

Fakhru'l-Razi Ahmadun, Ph.D.,  
Department of Chemical Engineering and Environment,  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Member)

Badlishah Sham Baharin,  
Associate Professor,  
Department of Food Technology,  
Faculty of Food Science and Biotechnology,  
Universiti Putra Malaysia  
(Member)

Shaari Mustapha, Ph.D.,  
Department of Chemical Engineering and Environment,  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Member)

Yaakob Che Man, Ph.D.,  
Professor,  
Department of Food Technology,  
Faculty of Food Science and Biotechnology,  
Universiti Putra Malaysia  
(Member)

  
\_\_\_\_\_  
MOHD. CHAZALI MOHAYIDIN, Ph.D.,  
Professor/Deputy of Graduate school,  
Universiti Putra Malaysia

Date: 8 OCT 2001

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science.




---

AINI IDERIS, Ph.D,  
Professor,  
Dean of Graduate School,  
Universiti Putra Malaysia

Date: **13** DEC 2001

## DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

  
\_\_\_\_\_  
Rusnani Abd. Majid  
Candidate

Date: 2 oktober 2001

## TABLE OF CONTENTS

	<b>Page</b>
ABSTRACT	ii
ABSTRAK	v
ACKNOWLEDGEMENTS	viii
APPROVAL SHEETS	x
DECLARATION FORM	xii
LIST OF TABLES	xvi
LIST OF FIGURES	xix
LIST OF PLATES	xxi
 <b>CHAPTER</b>	
 <b>1. INTRODUCTION</b>	 <b>1</b>
 <b>2. LITERATURE REVIEW</b>	 <b>7</b>
Palm Oil	7
Background	7
Production	9
End-uses of Palm Oil	13
Extraction of Palm Oil	15
Palm Oil Refining	18
Crude Palm Oil	28
Background	28
Free Fatty Acid	35
Carotene	35
Phospholipids	37
Heavy Metal Content	39
Membrane Technology	40
Definition of a Membrane	40
Membrane Separation Concept	40
Membrane Processes	40
Mechanism of Filtration	43
Membrane Structure	44
Membrane Material	45
Membrane Selections	46
Membrane Modules	46
Applications of Membrane Processes	50
Concentration Polarization and Fouling	55
Advantages of Membrane Technology	57
 <b>3. PROCESSING OF CRUDE PALM OIL WITH CERAMIC MICROFILTRATION MEMBRANE</b>	 <b>58</b>
Introduction	58
Materials and Methods	61
Materials	61



Microfiltration Equipment	61
Experimental Procedure	66
Analysis	67
Calculation	67
Results and Discussion	68
Effect of Membrane Processing on Quality of Palm Oil	68
Effect of Average Transmembrane Pressure on Permeation Flux	72
Effect of Feed Flow on Permeation Flux	73
Effect of Time on Permeation Flux	76
Summary	80
 <b>4. COMPARISAN STUDY ON THE IMPURITIES REMOVAL USING MEMBRANE PROCESS AND CONVENTIONAL REFINING PROCESS</b>	 81
Introduction	81
Materials and Methods	83
Samples	83
Crossflow Microfiltration System	84
Membrane	84
Batch Experimental	84
Cleaning Studies	85
Storage Study	86
Analysis	87
Results and Discussion	87
Quality of Membrane-permeate and Bleached Oils	87
Effect of Deodorization on Oil Quality	90
Stability of Free Fatty Acid and Peroxide Value during Storage	91
Cleaning Process	95
Summary	97
 <b>5. PROCESSING OF CRUDE PALM OIL WITH ULTRAFILTRATION CERAMIC MEMBRANE</b>	 99
Introduction	99
Materials and Methods	100
Materials	100
Membrane Processing	102
Cleaning Procedure	105
Analysis	106
Results and Discussion	106
Changes on Oil Quality	106
Effect of Average Transmembrane Pressure on Flux Rate	111
Effect of Variations of Feed Flow on Flux Rate	113
Effect of Processing Time on Flux Rate	116
Effect of Temperature on Flux Rate	117



	Cleaning	119
	Summary	122
<b>6.</b>	<b>SUMMARY, CONCLUSION AND RECOMMENDATION</b>	<b>124</b>
	Summary	124
	Conclusion and Recommendation	128
	<b>BIBLIOGRAPHY</b>	<b>131</b>
	<b>APPENDICES</b>	<b>143</b>
	<b>BIOGRAPHICAL SKETCH</b>	<b>156</b>

## LIST OF TABLES

Table	Page
2.1 Total Oil Palm Planted Area (Hectare)	9
2.2 World Palm Oil Production 1960 – 1999 (1,000 metric tons)	10
2.3 World Palm Oil Exports 1960 – 1999 (1,000 metric tons)	11
2.4 Malaysia Exports of Crude and Processed Palm Oil (1960 –1999)	12
2.5 Refining Crude Palm Oil – Unit Processes	22
2.6 Desirable Quality of DB and RBD Palm Oil	24
2.7 Desirable Quality of NPO, NBPO and NBDPO	25
2.8 PORAM Standard Specification for Processed Oil	26
2.9 Fatty Acid Composition of Palm Oil	29
2.10 Mean Identity Characteristics of CPO	30
2.11 Solid Fat Content of CPO	31
2.12 Traded Crude Palm Oil Quality	32
2.13 Survey Data of Crude Palm Oil Quality Characteristics	33
2.14 Guidelines for CPO Quality	34
2.15 Composition of Carotene in Palm Oil	36
2.16 Phospholipid Composition of Crude Palm Oil	38
2.17 Phospholipid, Inorganic Phosphates and Total Phosphorus in Crude Palm Oil	38
2.18 Comparison of Process-related Characteristics for Membrane Module Configurations	47
2.19 Commercial Membrane Applications in the Food Industry	52

3.1	Quality Requirements for Crude Palm Oil (CPO), Neutralized Palm Oil (NPO), Neutralized Bleached Palm Oil (NBPO) and Refined/Neutralized Bleached and Deodorized Palm Oil (RBD/NBP)	62
3.2	Specifications of the MF Membrane Module	65
3.3	Free Fatty Acid and Carotene of Membrane Processed Crude Palm Oil	70
3.4	Fatty Acid Composition of Membrane Processed Crude Palm Oil (0.2 $\mu\text{m}$ )	71
3.5	Phosphorus and Iron Contents of Membrane Processed Crude Palm Oil	72
3.6	FFA of Microfiltration-Processed (0.45 $\mu\text{m}$ ) Oil	144
3.7	Carotene Contents of Microfiltration-Processed (0.45 $\mu\text{m}$ ) Oil	144
3.8	Phosphorus Contents of Microfiltration-Processed (0.45 $\mu\text{m}$ ) Oil	145
3.9	FFA of Microfiltration-Processed (0.2 $\mu\text{m}$ ) Oil	145
3.10	Carotene Contents of Microfiltration-Processed (0.2 $\mu\text{m}$ ) Oil	146
3.11	Phosphorus Contents of Microfiltration-Processed (0.2 $\mu\text{m}$ ) Oil	146
4.1	Specifications of Membrane Module	84
4.2	Free Fatty Acid and Carotene Content of Membrane-Permeate And Commercial Bleached Oils	88
4.3	Phosphorus Content of Membrane-Permeate and Commercial Bleached Oils	90
4.4	Comparison Quality of Membrane-Processed Palm Oil and Conventional-Processed Palm Oil	92
4.5	FFA of Permeate and Bleached Oil	147
4.6	Carotene Content of Permeate and Bleached Oil	148
4.7	Phosphorus Content of Permeate and Bleached Oil	149
4.8	FFA of M-PO and C-PO	150
4.9	Carotene Contents of M-PO and C-PO	150

4.10	Effect of FFA Stability During Storage (MDPO)	151
4.11	Effect of Peroxide Value During Stability (MDPO)	152
4.12	Effect of FFA During Storage Stability (RBDPO)	153
4.13	Effect of Peroxide Value During Storage Stability (RBDPO)	154
5.1	Specifications of UF Membrane Module	102
5.2	Free Fatty Acid, Carotene, Phosphorus and Iron Content of Palm Oil Treated with Ceramic UF Membrane	108
5.3	Fatty Acid Composition of Palm Oil Treated with 20 nm UF Membrane	109
5.4	Fatty Acid Composition of Palm Oil Treated with 50 nm UF Membrane	110
5.5	Carotene Content in Permeates at Various Temperatures	120
5.6	Phosphorus of Ultrafiltration-Processed (20 nm) Oil	155
5.7	Phosphorus of Ultrafiltration-Processed (50 nm) Oil	155

## LIST OF FIGURES

Figure	Page
2.1 Fruit Component of Different Fruit Types	8
2.2 Uses of Palm Oil	14
2.3 Process Flow Diagram of A Palm Oil Mill	17
2.4 Oil Refining Stages	21
2.5 Membrane Concept	41
2.6 Principles of Membrane Separations	42
2.7 Mechanisms of Filtration; dead-end with cake formation and crossflow without cake formation	44
3.1 Schematic Diagram of Crossflow Microfiltration System	63
3.2 Effect of Transmembrane Pressure on Permeate Flux	74
3.3 Effect of Feed Flow on Permeate Flux	75
3.4 Membrane Fouling	76
3.5 Effect of Processing Time on Permeate Flux	77
3.6 Permeate Flux of Water and CPO at Various Transmembrane Pressures (0.45 micron)	78
3.7 Permeate Flux of Water and CPO at Various Transmembrane Pressures (0.2 micron)	79
4.1 The Effect of Membrane and Conventional Processing on the Stability of Free Fatty Acid (FFA)	93
4.2 The Effect of Membrane and Conventional Processing on the Stability of Peroxide Value (PV)	95
4.3 The Effect of Cleaning Process on the Clean Water Flux	97
5.1 Schematic Diagram of the Crossflow Ultrafiltration System	103

5.2	Permeate Flux at Various Transmembrane Pressures	113
5.3	Permeate Flux at Various Feed Rates	115
5.4	Permeate Flux Versus Time	117
5.5	Permeate Flux at Various Temperatures	119
5.6	Clean Water Flux Before Membrane Processing and After Cleaning (20 nm)	121
5.7	Clean Water Flux Before Membrane Processing and After Cleaning (50 nm)	122

## LIST OF PLATES

<b>Plate</b>		<b>Page</b>
2.1	Fresh Fruit Bunches (FFB)	16
3.1	Crossflow Microfiltration System	63
3.2	Ceramic Microfiltration Membrane (side view)	64
3.3	Ceramic Microfiltration Membrane (front view)	65
4.1	Crude Palm Oil (CPO), Membrane-Processed Palm Oil (M-PO) and Conventional-Processed Palm Oil (C-PO)	92
5.1	Ceramic Ultrafiltration Membrane (side view)	101
5.2	Ceramic Ultrafiltration Membrane (front view)	101
5.3	Crossflow Ultrafiltration System	104

## CHAPTER 1

### INTRODUCTION

Crude palm oil (CPO) is produced by extracting oil from fresh fruit bunches (FFB). The oil contains mainly triglycerides and some variables of impurities. Impurities which include phospholipids, free fatty acid (FFA), trace metals, oxidation products and sterols are detrimental to the oil's flavour, odour and colour. This undesired impurities needs to be removed or reduced as much as possible in order to be accepted as edible palm oil. However, some of the impurities such as tocopherol and tocotrienol, and carotene have nutritional values. Both tocopherol and tocotrienol function as natural antioxidants which help to protect the oil from oxidation and as vitamin E (Goh et al., 1987).  $\alpha$ - and  $\beta$ -carotene are precursors of vitamin A.

Two methods are available for the refining of CPO to produce refined, bleached and deodorized palm oil (RBDPO). They are chemical refining (neutralization with sodium hydroxide solution) and physical refining. Each method involves various stages of refining including degumming, bleaching and deodorizing. Each stage removes only one or two undesirable components. These steps require high capital cost equipment. In chemical refining, treatment with sodium hydroxide results in oil loss due to emulsification, oil occlusion in soapstock and saponification (Young, 1981). Large amount of water is required,



thus generates high amount of contaminated wastewater from the plant. The physical refining, which is preferable than chemical refining involves pretreatment (degumming and bleaching) and distillation processes. High temperature, high vacuum and direct steam injection are used to decompose the carotenoids pigments in palm oil and distil the breakdown compounds, fatty acids and oxidation products from the oil (Young, 1981).

For both chemical and physical refining, degumming process involves the usage of phosphoric acid and bleaching process involves addition of bleaching earth. Any excess of phosphoric acid which is not removed in the subsequent bleaching step will cause darkening of RBDPO (Thiagarajan and Tang, 1991). The level of phosphorus in RBD oils affects the rise of FFA and the increase in colour during storage. High levels of phosphorus in RBD oils with phosphoric acid during degumming may account for the colour deterioration in some “good” oils during storage, and form colour fixation during deodorization. These processes are energy-intensive and also produce waste by-products like spent bleaching earth, which may cause environmental problems unless properly treated.

In general, conventional refining of CPO requires the usage of chemicals such as phosphoric acid and bleaching earth for the treatment of the crude oil. During the process, bleaching earth trap some oil. According to Aziz (2000), the amount of oil loss in the refining process will also correspondent with the amount of bleaching earth during the bleaching process. The conventional refining consumes large amount of energy to heat and cool the oil as well as to provide